	d1 _{g8} mm	d2 _{z9} mm	d3 _{h9} mm	l1 mm	l2 mm	Z	Code 2150 Art.-Nr.
M 4	4,50	8,00	5,00	71	14	3	0 2150008001 00
M 5	5,50	10,00	8,00	80	18	3	0 2150010001 00
M 6	6,60	11,00	8,00	80	18	3	0 2150011001 00
M 8	9,00	15,00	12,50	100	22	3	0 2150015001 00
M10	11,00	18,00	12,50	100	22	3	0 2150018001 00
M12	13,50	20,00	12,50	100	22	3	0 2150020001 00


D Flachsenker für auswechselbare Führungszapfen, MK-Schaft, DIN 375

Einsatzbereich:
Für alle E- und NE-Metalle, Kunststoffe hart und weich. Zur Verwendung in Durchgangslöcher nach DIN 273 bei Einzel- und Serienfertigung.



E Counterbores for detachable pilots, MT-shank, DIN 375



Range of application:
For ferrous and non-ferrous metals, synthetic materials soft and hard, for working in through holes according to DIN 273. Suitable in individual and mass production.



I Allargatori con guida intercambiabile, Cono morse, DIN 375

Impiego:
Adatti per tutti i materiali ferrosi, non ferrosi plastiche dure e dolci, per fori passanti secondo DIN 273, sia per lavorazioni singole che di serie.



	d2 _{z9} mm	d3 mm	l1 mm	l2 mm		Z	Code 2160 Art.-Nr.
M10	18,00	5,00	140	25	2	3	0 2160018001 00
M12	20,00	5,00	140	25	2	3	0 2160020001 00
M14	24,00	6,00	150	30	2	3	0 2160024001 00
M16	26,00	8,00	180	35	3	3	0 2160026001 00
M18	30,00	8,00	180	35	3	3	0 2160030001 00
M20	33,00	10,00	190	40	3	3	0 2160033001 00
M24	40,00	10,00	190	40	3	3	0 2160040001 00



HSS-Senker
HSS countersinks
HSS svasatori